

<u>Performing Arts Division –</u> Technical Support Unit

East Kowloon Cultural Centre

60 Ngau Tak Kok Road, Kowloon, HK

Phone 852-3166 2800

Fax 852-3547 2698

CONTACTS

Jimmy FONG

Senior Manager (EKCC) 1 Direct Line 852- 3166 2801 Email jhwfong@lcsd.gov.hk

Joey CHO

Manager (EKCC) 2 Direct Line 852- 3166 2805 Email jhmcho@lcsd.gov.hk

Andy TSUI

Resident Technical Manager (EKCC) Direct Line 852- 3166 2825 Email ayotsui@lcsd.gov.hk

GENERAL SET-UP

The Hall operates on a 'bare-wall' touring policy.
That is, all equipment is normally set-up and struck within the booking period.
Hirers are reminded to allow sufficient preparation time to hang theatre masking, rig all overhead stage lighting and set up sound system.

Check with our Resident Technical Manager for any other equipment and technical enquiries.

East Kowloon Cultural Centre – The Hall FULL Technical Information

V. 2025.07.30 Page 1 of 9





EKCC The Hall is a multi-purpose hall with different possible stage settings, including proscenium, canopy with different sizes, extended stage and orchestral pit with two sizes; suitable for staging productions of different art forms.

DIRECTIONS

MTR

Kwun Tong Line, Kowloon Bay Station, Exit B

Bus:

Kowloon Bay Station (East Kowloon Cultural Centre) Bus Stop, Amoy Garden Bus Stop

From HK Island W:

Cross Harbour Tunnel → East Kowloon Corridor → Kai Tak Tunnel → Prince Edward Road East → Kwun Tong Road → Fuk To Street

From HK Island E:

Eastern Harbour Tunnel → Kwun Tong Bypass → Kai Fuk Road → Kai Cheung Road →Ngau Tau Kok Road → Fuk To Street

From New Territories

Lion Rock Tunnel / Tate's Cairn Tunnel →
Lung Cheung Road
→ Kwun Tong Road → Fuk To Street

Nearby Public Car Parks

Telford Plaza, Amoy Plaza, Lower Ngau Tau Kok Estate

LOADING

Clearance of truck: 4.70m (H)

Truck Occupancy: 2nos. 40-ft Container

Dock Height: 1.20m

Loading to Side Stage Shutter Opening:

4.90 x 3.85m (W x H)

Side Stage Shutter Opening: 5.00 x 3.00m (W x H)

.

Opening to side stage: 4.99 x 3.85m (W x H)

Opening to rear stage:

3.75 x 3.85m (W x H)

Broadcasting Vehicle Parking with Truck Occupancy

7.50 x 3.50m (W x D) (Share use)

STAGE ENTRANCE

Ngau Tau Kok Road, facing Amoy Garden

PARKING

Permit required

V. 2025.07.30

AUDITORIUM



Stalls:	1196 714
Balcony:	482
Wheelchair Space Stalls:	8
Removable Seating	
Small Pit Lift:	74
Large Pit Lift:	137
Row A & B	59

REVERBERATION TIME

(averages at 500Hz and 1kHz)

Theatre Mode (Proscenium Layout) 1.0-1.2s Concert Mode (Sound Canopy Layout) 1.3-1.5s

PROSCENIUM


Structural Opening 16.00 x 10.00m (W x H) Adjustable Teaser and 13.00 x 6.00m (W x H) min. Tormentor

ACOUSTIC SHELL

Small Enclosure for 62 musicians	130m ²
Medium Enclosure for 90 musicians	190m²
Large Enclosure for 105 musicians	219m ²

STAGE WIDTH

Centreline to stage right fire shutter	15.00m
Centreline to stage left wall	15.00m
Between fly floors	21.00m
Centreline to stage right fly floor	10.50m
Centreline to stage left fly floor	10.50m



STAGE DEPTH

Rear of Proscenium to rear-stage shutter 17.00m Rear of Proscenium to upstage limit of grid 15.60m Rear of Proscenium to orchestra pit edge 5.00m on centreline

STAGE HEIGHT

10.00m Clearance under technical gallery Clearance under grid 26.50m

FORESTAGE / ORCHESTRA PIT

Small curved forestage/pit lift area (with a loss of 74 60.00m² seats)

pit platform can be raised to stage level to form a

bigger forestage

Big curved forestage/pit lift area (with a loss of 137 105.00m²

pit platform can be raised to stage level to form a bigger forestage

STAGE FLOOR

Flat black hardboard 750kg/ m² SWL Traps in modules on main stage area 15.80 x 9.64m (W x D) No. of modules 49 in two sizes Capacity 700kg SWL

V. 2025.07.30 Page 3 of 9

SIDE STAGE

Opening (Stage Right) 12.70 x 9.00m (W x H)

Width 21.00m Depth 16.20m

REAR STAGE

Opening 15.90 x 9.00m (W x H)

Width 25.10m Depth 16.10m

STORAGE SPACE

Shared space with side and rear stage area

CROSSOVER

Rear of stage

FIRE CURTAIN

Rear of Proscenium

Between main stage and rear stage Between main stage and side stage

ALL fire shutters are fire safety installation and must not be obstructed by scenery or any other objects.

RIGGING - FORESTAGE

Roller Beam (with chain hoist) 5

Chain Hoist 10 (2 per beam)

Loading Capacity 1000kg Minimum Beam Spacing 0.60m

RIGGING - STAGE

Rigging System60 bars

Prior submission of fly cue plot will speed up the production process.

Fly cues updating will require additional time for computer input.

Bar diameter 48mm Bar interval 0.20m

See lineset schedule for location and availability.

Bar length 18.00m (extending to 20.00 m)

Capacity 650kg SWL

Side Bar 4 (2 per each side)

Bar length 12.4m Capacity 500kg SWL

Light Ladder Bar 2 (1 per each side)

Bar length 12.4m Capacity 500kg SWL

Roller Beam (with chain hoist) 5

Hoist 20 (4 per beam)
Capacity 500kg SWL

RIGGING - REAR STAGE

Roller beam (with chain hoist) 5

Chain hoists 15 (3 per beam)
Capacity 1000kg/m² SWL

V. 2025.07.30 Page 4 of 9

STAGE EQUIPMENT				
Stage Drapery				
House Curtain	Purple			20.00 x 10.00m
(Motor Fly in variable speed)	·			
Black masking	Leg	12	Flat	5.00 x 11.00m
(Wool Serge)	Border	6	Flat	20.00 x 5.00m
(*************************************	Half tab	_	Flat	10.00 x 10.00m
	Black backdrop	1	Flat	18.00 x 10.00m
	Side masking	10	Flat	4.00 x 10.00m
Cycloromo	Side masking	10	Flat	18.00 x 10.00m
Cyclorama Black Gauze		2	Flat	18.00 x 10.00m
			Flat	18.00 x 10.00m
White Gauze		2	гіаі	16.00 X 10.00111
Orchestra Riser	2.4 v4.2m (\M v.L)	6	202mm (U)	
	2.4 x1.2m (W x L)	6	203mm (H)	
No drilling or painting on the		10	407mm (H)	
platform.		10	610mm (H)	
	2-step Stairway	2		
Choir Riser	3 steps	7 sets		
Onon Riser	4 steps	7 sets	with Back Rail	
	4 эксрэ	7 3013	With Dack Itali	
Conductor's Chair		1		
Conductor's Podium		1 set		
Conductor's Stand		1		
Chair	Musician Chair	100		
Chair	Musician Chair	120		
	High Stool	10		
	Cellist Stool	20		
Music Stand	Dlask	100		
Music Stand	Black	120		
Musical Instrument	Concert Grand Piano	2	Steinway & Sons	Model D
Wusical Histiament	Concert Grand Fland	۷	(incur extra charg	
	Upright Piano	2	Yamaha YUS5	6)
	Timpani	1 set	Adams Profession	nal Congration II
	тіпрапі	1 301		
			(incur extra charg	e)
Dance Tile	Black	(Please a	allow time to lay the	e tiles during booking time)
for dance show only	Black	(1 10030 6	allow time to lay the	tiles during booking time)
lor darice show only				
Sprung Dance Floor	20.00 x 15.00m	(Please	allow time to lay the	e tiles during booking time)
for dance show only	20.00 X 10.00m	(1 10000	anow arrio to lay are	o theo during booking time;
Tor darice show only				
Stage Carpet	Green	2	14.50 x 6.50m	
for Chinese Opera only	0.00.1	_	1 1.00 X 0.00111	
Tor Offinese Opera offig				
Lectern		1		
Table		24	1.80 x 0.60m (W x	k D)
		=	•	
Lift and Ladder	Lifting Platform	5		petent persons & prior
			approved by venu	ie management only

V. 2025.07.30 Page 5 of 9

persons*
POICOITO
persons*
persons*
persons*
persons#
persons*
persons*
persons*



Production Office Green Room

Quick change room at stage right and stage left. Temporary quick change facilities are available

RUNNING WARDROBE

3 washing machines, 3 dryers, located at Running Wardrobe at LG/F.

Sewing machine, iron & board and steamer can be loaned from Resident Stage Management Section.

LIGHTING

Power Circuit (in True1 Socket)	ETC Digital Dimmer, 3kW ETC Digital Dimmer, 5kW ETC Sensor3 Digital ThruPower Dimmer, 3kW ETC Sensor3 Digital ThruPower Dimmer, 5kW ETC Sensor3 Relay Power Control Modules	150 14 340 16 380
Additional Power	100A 3-phase Socket 63A 3-phase Socket 32A 3-phase Socket	2 4 4

Connection must be conducted by a local registered electrical worker. Hirer shall supply adequate circuit protective devices for all bring in electrical installations.

Control Board GrandMA3 Full, located in Lighting Control Room.

Portable Console GrandMA3 Light

House Light DMX controlled. Controlled independently or via control board in Lighting Control Room.

Profile	750W	ETC	Source 4 15/30°	30
	750W	ETC	Source 4 25/50°	20
LED Profile	305W	ETC	Source 4 Lustr 3	40
Fresnel	250W	Silver Star	SS826XH	40
	360W	Robert Juliat	Fresnel ZEP2	50
	167W	ETC	Source 4 Lustr 2	20
LED Automated Lighting	887W 930W 600W	ETC ETC ETC	SolarFrame 1000 SolaWash 1000 Sola Hybeam 1000	30 30 10

[#] Dressing room fitted with accessible toilet and shower

^{*} Dressing room fitted with toilet and shower

[^] Dressing room fitted with changing compartment

V. 2025.07.30 Page 6 of 9

PAR	1kW 180W	Kupo Silver Star	PAR64-FB SS352XCEM	50 20	
Cyclorama Light	400W	Altman	Spectra 400	8	
Ground Row	400W	Altman	Spectra 400	8	*No Yoke
Follow Spot	2500W	Robert Juliat	Cyrano 1015BS: 3/80	4	
Strobe Light	740W	Martin	Atomic 3000 LED	4	
UV Light	120W	ADJ	UV COB Cannon 1X	4	
Fog Machine	1300W	Look Solutions	Viper NT	4	
Hazer	1500W	Smoke Factory	Tour Haze II	4	
Side light ladder o	n track			8	(4 on each side)
Side light tower *Height:Centre of ler	ns to floor	6 (top) 5 4 3 2 1 (bottom)	2485 mm* 2045 mm* 1605 mm* 1165 mm* 725 mm* 285 mm*		
Music Light		LED Dimmable		100	

Hirer will be provided with basic lighting only, unless sufficient preparation time is provided during booking period and based on the complexity of the intended operation.

Supply of above equipment subject to availability on receipt of a lighting plan, minimum 3 weeks prior to booking commencement. Equipment availability does vary slightly according to equipment conditions and maintenance. Check with Resident Technical Manager for any updates.

All bring-in "Electrical and Stage Lighting Equipment" to be used in LCSD performance venues, shall meet the requirements of "Code of Practice for Electricity (Wiring) Regulations (2020 Edition)". Please contact the venue management for any electrical safety concern. Website reference: http://www.emsd.gov.hk/emsd/eng/welcome/em_safety.shtml

SOUND

Sound System	Immersive Sound System	
	d&b audiotechnik Yi8	20
	d&b audiotechnik Yi12	10
	d&b audiotechnik Yi-SUB	8
	d&b audiotechnik Yi-10P	5
	d&b audiotechnik 8S	6
	d&b audiotechnik 10S	28
	d&b audiotechnik 12S	42
	d&b audiotechnik E8	21
	d&b audiotechnik Vi10P	5
	d&b audiotechnik Vi-SUB	5
	d&b audiotechnik B16-SUB	6
	d&b audiotechnik B22-SUB	2
Main Control Console	DiGiCo Q7T	
Second Console	DiGiCo Q7T	
Microphone tie line	Distributed	
		·

V. 2025.07.30 Page 7 of 9

Microsphana	Dunamia Vasal Mia	
Microphone	Dynamic Vocal Mic Shure SM58	4
	Shure Beta 58A	4
	Sennheiser e835S	2
	Beyerdynamic M88TG	2
	DPA 4018V-B-B01 d:facto	6
		4
	Shure Nexadyne NXN8/S	4
	Dynamic Instrument mic	0
	Shure SM57	2
	Shure Beta 57A	4
	AKG D112 MKII	1
	Condenser Mic	
	Audio-Technica AT4041	6
	Sennheiser MKH 8040	6
	Sennheiser MKH 8050	2
	Sennheiser MKH 8070	2
	Neumann KM184	6
	Neumann KM185	6
	Shure Beta 52A	1
	AKG C414 XLS	6
	DPA 4055	4
	Neumann U87 Ai	2
	Shure Beta 87A	2
	Miniature Instrument Mic	
	DPA 4099 Core Rock Kit	1
Wireless Microphone	Sennheiser Digital 6000 Wireless Mic System	
	Including: Handheld – SKM 6000	14
	Body Pack – SK6212	20
D.I.	BSS AR133	6
	RNDI	8
	RNDI-S	4
	Radial USB-Pro	4
	Radial SB-5	2
	rtadia 65 6	_
CD/SD/USB Playback	Denon DN-500BD MKII	2
	Tascam C500B	2
	Tascam CDR-250N	2
Digital Cinema Projector (DCP)	4K Resolution	1
Induction Loop	At auditorium	
Simultaneous Translation System	3 language infra-red wireless simultaneous trans	slation system
LED Surtitle Display System	Horizontal LED Display Board	2
	Location – on both sides of the proscenium Size of LED	205 x 102.5cm (W x H)
COMMUNICATION		,
	At atoma right (may fave about all interests and	om)
SM Desk	At stage right (max. four channels intercom syste	em)



V. 2025.07.30 Page 8 of 9

Intercom System Auditorium, stage and backstage

4-channel Main Station1 setWired Intercom18 setsWireless Intercom10 sets

Cue Light System Fixed positions – Technical area

Paging and Show Relay

System

Dressing room and backstage area

PROJECTION

Multimedia Projector Panasonic PT-RQ35K (at Designated Positions) 6

SERVER Media Server

VIDEO STREAMING & RECORDING

4K Video Filming & Image Processing System

Camera w/ Robotic Head Sony HDC-P50 (at Designated Positions) 2 Kxwell KT-RP8910 Robotic Head Control Portable Camera Stand Panasonic Polecam PanaPod 1 Video Switcher Sony XVS-G1 with 2M/E 16 Button Control Panel 1 Matrox Monarch Edge Streaming Encoder 1 Video Recorder BMD HyperDeck Studio 4K Pro 7

TRACKING Blacktrax

Zactrack Pro

Prior to the booking date, please confirm with Technical Manager the availability of the equipment. All required equipment will be set-up during the booking period; please allow adequate time in the production schedule for equipment set-up, tuning, alignment and test before rehearsal or performance.

V. 2025.07.30 Page 9 of 9

POOLED LIGHTIN	G EQUIPME	NT LIST (Shared I	by all venues)	
Profile	167W	ETC	Source 4 Lustr 2 Profile 15/30°	50
Fresnel	250W	Silver Star	SS826XH	16
LED Automated Lighting	887W 930W	HES HES	SolaFrame 1000 SolaWash 1000	30 10

MENT LIST (Shared by all yenuse)		
MENT LIST (Shared by all vehices)		
Dynamic Vocal Mic		
	4	
	•	
Shure Nexadyne NXN8/S	6	
Dynamic Instrument mic		
Shure SM57	1	
Shure Beta 57A	8	
AKG D112 MKII	1	
AKG SE 300B	1	
Condenser Mic		
Audio-Technica AT4041	6	
Sennheiser MKH 8040	6	
Sennheiser MKH 8050	4	
Sennheiser MKH 8070	2	
Neumann KM184	8	
Neumann KM185	8	
Shure Beta 52A	1	
AKG C414 XLS	8	
DPA 4055	4	
Neumann U87 Ai	1	
Shure Beta 87A	6	
Miniature Instrument Mic		
DPA 4099 Core Rock Kit	1	
DPA 4099 Core Class Kit X1	1	
	Dynamic Instrument mic Shure SM57 Shure Beta 57A AKG D112 MKII AKG SE 300B Condenser Mic Audio-Technica AT4041 Sennheiser MKH 8040 Sennheiser MKH 8050 Sennheiser MKH 8070 Neumann KM184 Neumann KM185 Shure Beta 52A AKG C414 XLS DPA 4055 Neumann U87 Ai Shure Beta 87A Miniature Instrument Mic DPA 4099 Core Rock Kit	Dynamic Vocal Mic Shure SM58 4 Shure Beta 58A 8 Sennheiser e835S 2 Beyerdynamic M88TG 1 DPA 4018V-B-B01 d:facto 4 Shure Nexadyne NXN8/S 6 Dynamic Instrument mic Shure SM57 1 Shure Beta 57A 8 AKG D112 MKII 1 AKG SE 300B 1 Condenser Mic Audio-Technica AT4041 6 Sennheiser MKH 8040 6 Sennheiser MKH 8050 4 Sennheiser MKH 8070 2 Neumann KM184 8 Neumann KM185 8 Shure Beta 52A 1 AKG C414 XLS 8 DPA 4055 4 Neumann U87 Ai 1 Shure Beta 87A 6 Minitature Instrument Mic DPA 4099 Core Rock Kit 1

Multimedia Projector & Lens	Panasonic PT-RQ35KE
	Lens ET-D75LE8 - 7.3-13.8:1

POOLED PROJECTION EQUIPMENT LIST (Shared by all venues)

Lens ET-D75LE10 – 1.3-1.7:1 Lens ET-D75LE20 – 1.67-2.4:1 Lens ET-D75LE30 – 2.4-4.7:1 Lens ET-D75LE40 – 4.6-7.1:1 Lens ET-D3LEW60 – 0.9-1.1:1 Lens ET-D3LEU100 – 0.37:1

Equipment on this list is allocated on a <u>first come first served</u> basis, on presentation of a complete production planning and work flow schematics.

Pool equipment cannot be reserved for any pending designs.