

Performing Arts Division -Technical Support Unit

East Kowloon **Cultural Centre**

60 Ngau Tau Kok Road, Kowloon, HK

Phone 852-3166 2800

852-3547 2698

CONTACTS

Jimmy FONG

Senior Manager (EKCC) 1 Direct Line 852-3166 2801 Email jhwfong@lcsd.gov.hk

Joey CHO

Manager (EKCC) 2 Direct Line 852-3166 2805 Email jhmcho@lcsd.gov.hk

Andy TSUI

Resident Technical Manager (EKCC) Direct Line 852-3166 2825 Email ayotsui@lcsd.gov.hk

GENERAL SET-UP

The Theatre operates on a 'barewall' touring policy. That is, all equipment is normally set-up and struck within the booking period. Hirers are reminded to allow sufficient preparation time to hang theatre masking, rig all overhead stage lighting and set up sound system.

Check with our Resident Technical Manager for any other equipment and technical enquiries.

East Kowloon Cultural Centre - The Theatre **FULL** Technical Information

V. 2025.09.19



EKCC The Theatre is a thrust stage setting brings performers closer to the audience, creating a more intimate and interactive performance environment.

Page 1 of 9



DIRECTIONS

Kwun Tona Line Kowloon Bay Station, Exit B

Kowloon Bay Station (East Kowloon Cultural Centre) Bus Stop, Amoy Gardens Bus Stop

From HK Island W:

Cross Harbour Tunnel → East Kowloon Corridor → Kai Tak Tunnel → Prince Edward Road East → Kwun Tong Road → Fuk To Street

From HK Island E:

Eastern Harbour Tunnel → Kwun Tong Bypass → Kai Fuk Road → Kai Cheung Road →Ngau Tau Kok Road → Fuk To

From New Territories

Lion Rock Tunnel / Tate's Cairn Tunnel → Lung Cheung Road → Kwun Tong Road → Fuk To Street

Nearby Public Car Parks

Telford Plaza, Amoy Plaza, Lower Ngau Tau Kok Estate

LOADING

Clearance for truck: 4.70m (H)

Truck Occupancy: 2 nos. 20-ft Container

Dock Height: 1.20m

Loading to Rear Stage Shutter Opening:

3.65 x 3.70m (W x H)

Opening to rear stage:

3.42 x 3.02m (W x H)

STAGE ENTRANCE

Ngau Tau Kok Road, facing Amoy Plaza

PARKING

Permit required

V. 2025.09.19 Page 2 of 8

AUDITORIUM



Total Seating 536 Wheelchair Space: 4

REVERBERATION TIME 0.9-1.1s

(averages at 500Hz and 1kHz):

PROSCENIUM

Structural Opening to 10.80 x 7.00m (W x H)

upstage area

Adjustable Portal 7.20 x 4.90m (W x H) min.

STAGE WIDTH

Centreline to stage right edge 4.25m
Centreline to stage left edge 4.25m




Front stage edge to upstage edge of trap 12.00m module

Front stage edge to upstage wall 16.90m

STAGE HEIGHT

Thrust - Clearance under technical gallery 7.95m
Behind Structural Opening - Clearance 15.00m
under upstage grid
Above Auditorium 0.42m



STAGE FLOOR

STAGE

Flat black hardboard 750kg/ m² SWL Traps in modules on stage area 46 No. of modules 48

REAR STAGE

Width 21.50m Width between the galleries 21.700m

Depth

Structural Opening to back wall

7.50m
Structural Opening to crossover gallery

4.25m

Height

Clearance under crossover gallery 9.60m

STORAGE SPACE

Backstage area

CROSSOVER

Ring corridor connecting vomitories, backstage and understage

V. 2025.09.19 Page 3 of 8

RIGGING - Stage

Roller Beam (with chain hoist) 15

15 (1 per beam) Hoist **Loading Capacity** 500kg SWL Minimum Beam Spacing 0.60m

Lighting Bar on Technical Gallery 50kg/m SWL

RIGGING - Upstage

Rigging System

Prior submission of fly cue plot will speed up the production process. Fly cues updating will require additional time for computer input.

48mm Bar diameter 0.20m Bars interval

See lineset schedule for location and availability.

Bar length 12.00m (4 bars)

7.00m (1 bar)

Loading Capacity 650kg SWL for 12.00m

500kg SWL for 7.00m

Side Bar 2 (1 on each side)

Bar diameter 48mm Bar length 3.40m Loading Capacity 300kg SWL

Light Ladder Bar 2 (1 on each side)

Bar length 2.00m Loading Capacity 300kg SWL

Upstage Grid

Chain Hoist Track (with chain hoist)

4 (1 per beam) Hoist 500kg SWL Capacity

RIGGING - Rear Stage

Chain Hoist Track (with chain hoist)

4 (1 per beam) Hoist Capacity 500kg SWL

Legs

STAGE EQUIPMENT

Stage Drapery

Masking

House Curtain	6.50 x 8.00m

	Borders	2	Flat	14.00 x 3.50m
	Half tab	2	Flat	7.00 x 7.00m
	Side Masking	4	Flat	4.00 x 8.00m
Cyclorama		1	Flat	12.00 x 7.00m
Black Gauze		1	Flat	12.00 x 7.00m

White Gauze Flat 12.00 x 7.00m 1

Choir Riser 3 steps 3 sets

> 4 steps 3 sets with Back Rail

4

Flat

4.00 x 7.00m

Chair Musician Chair 40

High Stool 5

Music Stand Black 40

Musical Instrument Concert Grand Piano Steinway & Sons (incur extra charge) 1

V. 2025.09.19 Page 4 of 8

Lectern	1

Table 12 1.80 x 0.60m (W x D)

Lift and Ladder Lifting Platform 2

DRESSING ROOM

	<u> </u>	<u></u>
G/F	T1	15 persons [^]
(Stage)	T2	2 persons#
	Т3	2 persons#
	T4	2 persons*
	T5	2 persons*
	Т6	6 persons#
	T7	10 persons*
	T8	8 persons#

Production Office Green Room

[^] Dressing rooms fitted with changing compartment.
Temporary quick change facilities are available by request.



Operated by competent persons & prior

RUNNING WARDROBE

Washing machines, dryers, located between dressing room T5 & T7.

Sewing machines, iron & boards, and steamers can be loaned from Resident Stage Management Section.

LIGHTING

Power Circuit	ETC Digital Dimmer, 3kW	30
(in True1 socket)	ETC Digital Dimmer, 5kW	4
(III True I Socket)	ETC Sensor3 Digital ThruPower Dimmer, 3kW	79
	ETC Sensor3 Digital ThruPower Dimmer, 5kW	5
	ETC Sensor3 Relay Power Control Modules	95
Additional Power	63A 3-phase Socket	1

Connection must be conducted by a local registered electrical worker. Hirer shall supply adequate circuit protective devices for all bring-in electrical installations.

Control Board grandMA3 Light console located in Lighting Control Room.

Portable Console grandMA3 Light

House Light DMX controlled, controlled via control board in Lighting Control Room.

Profile	750W 750W	ETC ETC	Source 4 Profile 15/30° Source 4 Profile 25/50°	20 16
LED Fresnel	167W	ETC	Source 4 Lustr 2 Fresnel	20
LED Automated Lighting	400W 480W 440W 850W	HES HES HES Robe	SolaPix 7 SolaWash 1000 SolaHyBeam 1000 T2 Profile	16 18 10 20
PAR	180W 1kW	Silver Star Kupo	SS352XCEM PAR64-FB (CP61)	30 20
Cyclorama Light	400W	Altman	Spectra 400	4

[#] Dressing rooms fitted with accessible toilet and shower

^{*} Dressing rooms fitted with toilet and shower

V. 2025.09.19 Page 5 of 8

Ground Row	400W	Altman	Spectra 400	4	*No Yoke
Strobe Light	740W	Martin	Atomic 3000 LED	2	
UV Light	120W	ADJ	UV COB Cannon 1X	2	
Fog Machine	1300W	Look Solutions	Viper NT	2	
Hazer	1500W	Smoke Factory	Tour Haze II	2	
Side Light Ladder				2	
Side Light Tower *Height: Centre of ler	ns to floor	6 (top) 5 4 3 2 1 (bottom)	2485 mm* 2045 mm* 1605 mm* 1165 mm* 725 mm* 285 mm*	4	

Hirer will be provided with basic lighting only, unless sufficient preparation time is provided during booking period and based on the complexity of the intended operation.

Supply of above equipment subject to availability upon receipt of a lighting plan, minimum 3 weeks prior to booking commencement. Equipment availability does vary slightly according to equipment conditions and maintenance. Check with Resident Technical Manager for equipment updates.

All bring-in "Electrical and Stage Lighting Equipment" to be used in LCSD performance venues, shall meet the requirements of "Code of Practice for Electricity (Wiring) Regulations (2020 Edition)". Please contact the venue management for any electrical safety concerns. Website reference:

http://www.emsd.gov.hk/emsd/eng/welcome/em_safety.shtml

SOUND			
Sound System	Main System		
(Dante-based System)	d&b audiotechnik Vi10P	8	(Fix-installed)
	d&b audiotechnik Vi-SUB	4	(Fix-installed)
	Fill System		
	d&b audiotechnik E8	14	(Fix installed)
			(Fix-installed)
	d&b audiotechnik 44S	11	(Fix-installed)
	Surround System		
	d&b audiotechnik E8	16	(Fix-installed)
	Processor		
	d&b audiotechnik DS100 Signal Engine	1	
Stage Monitor	d&b audiotechnik M4	10	
Amplifier	d&b audiotechnik 10D	2	(Fix-installed)
	d&b audiotechnik 30D	3	(Fix-installed)
Main Control Console	DiGiCo SD12		
mam control concolo	Mono Inputs	32	
	Stereo Inputs	16	
	Aux / Subgroup Outputs	12	
Second Console	DiGiCo SD12	1	
Miaranhana tia lina		0.4	
Microphone tie line	Each side of the stage	24	
	Upstage Centre	8	
	Auditorium	8	

V. 2025.09.19 Page 6 of 8

Missonbox	Dunamia Vasal Mic	
Microphone	Dynamic Vocal Mic Shure SM58	4
	Shure Beta 58A	4
	Sennheiser e835S	4 2
	Beyerdynamic M88TG	2
	DPA 4018V-B-B01 d:facto	6
		4
	Shure Nexadyne NXN8/S	4
	Dynamic Instrument mic	
	Shure SM57	2
	Shure Beta 57A	4
	AKG D112 MKII	1
	Condenser Mic	4
	Audio-Technica AT4041	4
	Sennheiser MKH 8040	6
	Sennheiser MKH 8050	2
	Sennheiser MKH 8070	2
	Neuman KM184	6
	Neuman KM185	6
	Shure Beta 52A	1
	AKG C414 XLS	6
	DPA 4055	4
	Shure Beta 87A	2
	Miniature Instrument Mic	
	DPA 4099 Core Class Kit X1	1 set
Wireless Microphone	Sennheiser Digital 6000 Wireless Mic System	
Wileless Microphone	Including: Handheld – SKM 6000	8
	Body Pack – SK6212	8
D.I.	BSS AR 133	2
	RNDI	8
	RNDI-S	4
	Radial USB-Pro	4
	Radial SB-5	2
	Nadiai OD-3	Z
CD/SD/USB Playback	Denon DN-500BD MKII	2
	Tascam CD500B	2
	Tascam CDR-250N	2
Induction Loop	Auditorium Area	
Simultaneous Translation	3-language infra-red wireless simultaneous translation	on system
System	(incur extra charge)	on system
Jotom	(modi oxid ondigo)	
LED Surtitle Display System	Horizontal LED Display Boards	2
Curtille Display Cystelli	Location - On both sides of the proscenium	2
	Size of LED Board	205 x 102.5 cm (W x H)
	OIZO OI LED DOGIU	200 A 102.0 OIII (VV X 11)
COMMUNICATION		
SM Desk	At stage right (max. four channels intercom system)	
Intercom System	Auditorium, stage and backstage	
	4-channel Main Station	1 set
	Wired Intercom	10 sets
	Wireless Intercom	8 sets
	THOOS INCION	0 0010
Cue Light System	Portable	8 sets



V. 2025.09.19 Page 7 of 8

Paging and Show Relay Dressing room and backstage area **System PROJECTION Multimedia Projector** Panasonic PT-RQ35KE (at Designated Positions) **SERVER Media Server VIDEO STREAMING & RECORDING** Streaming PTZ Camera Panasonic AW-UE160 (at Designated Positions) 7 2 Remote Control Panel Panasonic AW-RP150 2 Panasonic Polecam PanaPod Camera Stand Sony XVS-G1 with 1M/E 16 Button Control Panel Video Switcher 1 Streaming Encoder Matrox Monarch Edge 1 Video Recorder BMD HyperDeck Studio 4K Pro 9 **TRACKING** Blacktrax Zactrack Pro

Prior to the booking date, please confirm with Technical Manager the availability of the equipment. All required equipment will be set-up during the booking period; please allow adequate time in the production schedule for equipment set-up, tuning, alignment and test before rehearsal or performance.

V. 2025.09.19 Page 8 of 8

POOLED LIGHTING	G EQUIPME	NT LIST (Shared I	oy all venues)	
Profile	167W	ETC	Source 4 Lustr 2 Profile 15/30°	50
Fresnel	250W	Silver Star	SS826XH	16
LED Automated Lighting	480W 480W	HES HES	SolaFrame 1000 SolaWash 1000	30 10

1icrophone	Dynamic Vocal Mic		
•	Shure SM58	4	
	Shure Beta 58A	8	
	Sennheiser e835S	2	
	Beyerdynamic M88TG	1	
	DPA 4018V-B-B01 d:facto	4	
	Shure Nexadyne NXN8/S	6	
	Dynamic Instrument mic		
	Shure SM57	1	
	Shure Beta 57A	8	
	AKG D112 MKII	1	
	AKG SE 300B	1	
	Condenser Mic		
	Audio-Technica AT4041	6	
	Sennheiser MKH 8040	6	
	Sennheiser MKH 8050	4	
	Sennheiser MKH 8070	2	
	Neumann KM184	8	
	Neumann KM185	8	
	Shure Beta 52A	1	
	AKG C414 XLS	8	
	DPA 4055	4	
	Neumann U87 Ai	1	
	Shure Beta 87A	6	
	Miniature Instrument Mic		
	DPA 4099 Core Rock Kit	1	
	DPA 4099 Core Class Kit X1	1	

POOLED PROJECTION EQUIPMENT LIST (Shared by all venues)			
Multimedia Projector & Lens	Panasonic PT-RQ35KE		
	Lens ET-D75LE8 - 7.3-13.8:1		
	Lens ET-D75LE10 - 1.3-1.7:1		
	Lens ET-D75LE20 - 1.67-2.4:1		
	Lens ET-D75LE30 - 2.4-4.7:1		
	Lens ET-D75LE40 – 4.6-7.1:1		
	Lens ET-D3LEW60 - 0.9-1.1:1		
	Lens ET-D3LEU100 – 0.37:1		

Equipment on this list is allocated on a <u>first come first served</u> basis, on presentation of complete production planning and work flow schematics.

Pool equipment cannot be reserved for any pending designs.